

**SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017**

**Shielding Integrity Services**

4750 North Chestnut Street  
Colorado Springs, CO 80907

Adam Vankeuren

Phone: 719-635-7719

Email: adam.vankeuren@chambertest.com

<https://chambertest.com/>

**ELECTROMAGNETIC COMPATIBILITY &  
TELECOMMUNICATIONS**

**NVLAP LAB CODE 200974-0**

**Emissions**

**Designation**

ETSI TR 102 273-2 V1.2.1  
(2001-12)

ETSI TR 102 273-3 v1.2.1  
(2001-12), Parts 6.4.1-6.4.3 only

EN 50147-1 (1997)

EN 50147-2 (1997)

ANSI C63.4a (2017)

ANSI C63.4 (2014)

**Description**

Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber

(ERM) - Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties. Part 3: Anechoic chamber with a ground plane.

*Section 6.4.1 - 30 MHz - 1000 MHz*

*Section 6.4.2 - Alternative procedure: 30 MHz to 1000 MHz*

*Section 6.4.3 - 1 GHz to 12.75 GHz*


Anechoic chambers. Shield attenuation measurement

Anechoic chambers. Alternative test site suitability with respect to site attenuation

American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz--Amendment 1: Test Site Validation

*NSA Only (30MHz - 1GHz)*

American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment - NSA Only (30MHz - 1GHz)



*For the National Voluntary Laboratory Accreditation Program*

## ELECTROMAGNETIC COMPATIBILITY &

### TELECOMMUNICATIONS

**NVLAP LAB CODE 200974-0**

ANSI C63.4 (2009)	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electrical Equipment - NSA only (30 MHz to 1GHz)
CISPR 16-1-4, Ed. 4.1 (2020-06)	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements  <i>Sections 6 and 7</i>
CISPR 16-1-4 (2019)	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements  <i>Sections 6 and 7</i>
CISPR 16-1-4 (2010) + A1 (2012), Clauses 8.3.3 through 8.4	Site VSWR (SVSWR) - 1GHz - 18 GHz: Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
CISPR 16-1-4 (2010) + A1 (2012) + A2 (2017), Clause 8	Site VSWR (SVSWR) - 1GHz - 18 GHz: Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
CISPR 16-1-4 (2010) + A1 (2012) + A2 (2017), Clause 5	Normalized Site Attenuation (NSA) - 30 MHz - 1 GHz: Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
CISPR 16-1-4 (2010), Clauses 5.2.6 - 5.4.3	Normalized Site Attenuation (NSA) - 30 MHz - 1 GHz: radio disturbance and immunity measurement apparatus and methods
CISPR 16-1-4 (2010), Clause 5.5.2	Set-up Table Influences - Radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
IEC/CISPR 25 (2016)	Vehicles, boats and internal combustion engines - Radio disturbance characteristics - Limits and methods of measurement for the protection of on-board receiver - Annex J - ALSE performance validation 150 kHz to 1 GHz
IEC/CISPR 25, Ed. 3.0 (2008-03)	Radio disturbance characteristics for the protection of receivers used on board vehicles, boats, and on devices - Limits and methods of measurement. NSA only. (70 MHz to 1GHz)
IEEE Std 149-1979 (R2008)	VSWR/Free Space - 30 MHz to 100 GHz: Test Procedure for Antennas
IEEE Std 299 (2006)	Measuring the Effectiveness of Electromagnetic Shielding Enclosures
NSA NO. 94-106 (1994-10)	Radio Frequency (RF) for Shielded Enclosures

## Immunity

### Designation

### Description

---

## ELECTROMAGNETIC COMPATIBILITY &

### TELECOMMUNICATIONS

NVLAP LAB CODE 200974-0

IEC 61000-4-3, Ed. 4.0 (2020-09)	Electromagnetic compatibility (EMC) - Part 4-3: Testing measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test
IEC 61000-4-3, Ed. 4.0	Field of Uniformity (FoU) - 26 MHz to 18 GHz
IEC 61000-4-3, Ed. 3.2	Field of Uniformity (FoU) - 26 MHz to 18 GHz
IEC 61000-4-21 (2011)	Electromagnetic compatibility (EMC) - Part 4-21: Testing and measurement techniques - Reverberation chamber test methods
IEC 61000-4-21, 1st Edition (2003-08)	EMC-Part 4-21: Testing and measurement techniques Reverberation chamber test methods

### MIL-STD

#### Designation

#### Description

MIL-STD-188-125-1 Appendix A	Shielding Effectiveness (SE) Test Procedures for Fixed Facilities
------------------------------	---

### MIL-STD: Radiated Emissions

#### Designation

#### Description

MIL-STD-188-125-2 Appendix A	Shielding Effectiveness (SE) Test Procedures for Transportable Ground-based Systems
------------------------------	---